

### $\mathbf{C}$ reen ess

# Mint 7240

### **BATTERY SYSTEM**

#### UNLEASH VERSATILITY

Custom connectors enable flexible use in series or parallel, adapting seamlessly to diverse energy storage needs—ESS, motorcycle, tricycle, and more.

#### SAFE POWER

GreenVolt S.G.S.C. technology delivers rapid discharge, efficient recharging, and dual-level output protection for secure, reliable energy storage and cost savings.

www.greeness.com.au

# $\mathbf{G}$ reen ess



Model	Mint 7240
Technical Specifications	Standard Parameter
Net weight	25kg (+/- 1 kg)
Dimensions	226x157.5x470mm
Installed Energy	40Ah / 2944Wh
Nominal Voltage	73.6 V
Nominal Capacit	2870.4Wh(39Ah)
Usable Battery Capacity	2296.32Wh
Rated DC Power	2.87kW
Configuration	23S2P
Charging Cut-off Voltage	82.8V
Discharging Cut-off Voltage	63V
Max Continuous Charging Current	39A
Max Continuous Discharge current	118A
Battery Chemistry	LiFePO4
Cycle Life	8000 cycles Condition: Max. 0.5C charge/discharge at 25±2°C Depth of Discharge (DoD) :80%
IP Rating	IP67
Operating Temperature	-30°C to +50°C
Storage Temperature	-42°C to +70°C
Humidity Range	5%~95%
Certificate	IEC 62619,IEC/EN 62040-1
Warranty	120 Months (Refer to warranty documents for conditional application.)
Country of Manufacture	China